

Xcelion® 56V-P

Rechargeable Li-ion battery system

SUPER LITHIUM-IRON PHOSPHATE HIGH POWER BATTERY

The Xcelion® 56V-P battery provides operating voltage from 40 - 60V and is useful for 48V applications such as electric mobility and stationary power.

This ruggedized battery uses Saft's proprietary Super-Phosphate® chemistry which is ideally suited for high performance applications requiring high levels of safety.



Benefits

- Significant weight savings and life cycle costs compared to lead-acid chemistries
- Maintenance free
- Commercial off-the-shelf solution
- Communicates over J1939 CAN Bus protocol
- Compatible with MIL-STD-1275E power bus

Features

- Built-in self-balancing
- Fast charging under varying conditions*
- Self shut-down in unsafe conditions
- Internal battery management system

Applications

- Stationary power
- Electric mobility
- Applications requiring balance of power and energy

Electrical characteristics

Nominal capacity	30 Ah
Nominal voltage	52.8 V
Voltage at full state of charge	60.8 VDC
Voltage at zero state of charge	40.0 VDC
Energy	1.6 kWh
Maximum discharge current	
Continuous	200 A
Pulse (25 ms)	1,500 A
Maximum charge current	
Continuous	125 A
Pulse (20s)	200 A

Mechanical characteristics

Weight	20.7 kg
Height	230 mm
Width	256 mm
Length	269 mm
Terminals	M8 Thread

Operating conditions

Operating temperature	
Discharge	-40°C to +60°C
Charge*	
Storage and transportation temperature**	-46°C to +71°C

*Battery manages charge energy to ensure maximum battery life. At low temperature, the battery will automatically engage built-in heaters for optimum charging.

**Sustained high temperature storage will reduce life.



Xcelion[®] 56V-P

Rechargeable Li-ion battery system

SUPER LITHIUM-IRON PHOSPHATE HIGH POWER BATTERY

Top level system functions

- Graphical User Interface Tool allows detailed view of battery status
- Communication of battery state of charge, temperature, and other key parameters via J1939 CAN Bus
- Redundant overcharge protection
- Overload protection
- Short circuit protection
- Over-discharge protection
- Battery reserve protection
- Battery monitoring
- Built-in-Test
- Cell heating (allows full battery capability over operating temperature)
- Continuous cell balancing

Safety heritage

- System design includes Saft's field proven electronic control architecture that includes overcharge protection, and over discharge, over temperature and overload protection.
- Cells equipped with hermetic seal and over pressure safety vent.
- Rechargeable Li-FePO₄ cells ideally suited for applications requiring high discharge, continuous or pulse power, fast re-charge, long cycle and calendar life, and high levels of safety.



Saft

26, quai Charles Pasqua
92300 Levallois-Perret - France
www.saftbatteries.com

Saft, a subsidiary of TotalEnergies SE
S.A.S. au capital de 31 944 000 euros
RCS NANTERRE 383.703.873